

壓力錶系列

標準型  壓力: 0 - 0.6 bar 0 - 400 bar 錶徑: 40, 50, 63, 80, 100, 160 mm 外殼: ABS、銅	重載型  壓力: 0 - 6 mbar 0 - 1600 bar 錶徑: 63, 80, 100, 160 mm 外殼: ABS、不銹鋼	超高壓型  壓力: 0 - 1600 bar 0 - 10000 bar 錶徑: 100, 160 mm 外殼: 不銹鋼	高精密型  壓力: 0 - 0.6 bar 0 - 1600 bar 錶徑: 160, 250 mm 外殼: 不銹鋼	電接點型  壓力: 0 - 1 bar 0 - 10000 bar 錶徑: 100, 160 mm 材質: 不銹鋼	化學密封型  壓力: 0 - 16 mbar 0 - 40 bar 錶徑: 100, 160 mm 外殼: 不銹鋼
---	---	---	---	--	--

壓力傳感器系列

一般應用型  壓力: -1 + 1600 bar 0 - 40 bar (絕壓) 外殼: 不銹鋼 輸出: 4 - 20 mA 0 - 5 (10) VDC	高精度型  壓力: -1 + 1000 bar 外殼: 不銹鋼 輸出: 0 (4) - 20 mA 0 - 5 (10) VDC	防爆型  壓力: -1 + 1000 bar 0 - 8000 bar 輸出: 4-20mA/0-10VDC 外殼: 不銹鋼 ATEX防爆等級: EExia I/IIc T6	食品工業用型  壓力: -1 + 25 bar 外殼: 不銹鋼 輸出: 0 (4) - 20 mA 0 - 10 VDC	制冷及通風行業用 OEM 型  壓力: -1 + 60 bar 外殼: 不銹鋼、銅 輸出: 4 - 20 mA 0 - 10 VDC 0.5 - 4.5 VDC	投入型測量  壓力: 0 - 25 bar 外殼: 不銹鋼 輸出: 0 (4) - 20 mA
---	---	---	---	--	---

壓力開關系列

機械式壓力開關  可調壓力: 0.2 - 400 bar 材質: 黃銅, 鍍鋅鋼, 不銹鋼	真空壓力開關  可調壓力: -0.85 + 1 bar 材質: 鍍鋅鋼, 不銹鋼 溫度範圍: -10 + 80°C	電子壓力開關  可調壓力: 0.005 - 600 bar 材質: 不銹鋼, 黃銅, 陽極氧化鋁	數字壓力計  壓力: -1 + 10 bar 0 - 700 bar 外殼: 不銹鋼 精度: 0.5% of FS	手持式壓力測量儀錶  壓力: -1 + 0 mbar 0 - 2000 mbar 精度: 0.2% / 0.1% LCD 顯示: 2 X 4 位	智能壓力變送器  過載壓力: 0 - 0.4 bar 0 - 4000 bar 絕對壓力: 0 - 0.4 bar 0 - 16 bar
---	---	---	--	---	---

數字顯示測量錶

機械式溫度計系列

雙金屬溫度計重型  溫度: -20 + 500°C 錶徑: 63, 80, 100 mm 外殼: 不銹鋼	化學型雙金屬溫度計  溫度: -70 + 30°C 0 - 500°C 錶徑: 3", 5" 外殼: 不銹鋼	化學型氣動式溫度計  溫度: -200 + 50°C 0 - 700°C 錶徑: 100, 160 mm 外殼: 不銹鋼	旋入式熱電偶型電阻溫度計  PT100: -200 + 600°C 熱電偶: 0 - 800°C 材質: 不銹鋼	電纜式電阻型溫度計  溫度: -200 + 1200°C 探針長度 (帶螺紋): 30, 50, 100, 200 mm 探針直徑: Φ3, 4, 6 mm 接線: 2 線 / 3 線 / 4 線	PT 電阻溫度計 (OEM)  溫度: -20 + 120°C 材質: 不銹鋼 輸出: 4 - 20 mA
---	---	---	--	---	---

電氣式溫度計系列

機械式測力度錶系列

液壓式壓力式力度錶  力度: 0 - 1 kN 0 - 2500 kN 錶徑: 10, 40, 100, 250 mm 材質: 不銹鋼	液壓環形力度錶  力度: 0 - 8 kN 0 - 2500 kN 錶徑: 40, 60, 90, 160, 240, 410 mm 外殼: 不銹鋼	液壓環形力度錶 (緊湊型)  力度: 0 - 320 N 0 - 120 kN 錶徑: 20 mm 外殼: 不銹鋼	測壓力  力度: 1 - 1000 kN 材質: 不銹鋼 輸出: 2 mV/V 0 (4) - 20 mA 0 - 10 VDC	測拉力  力度: 5 - 10000 kN 材質: 不銹鋼 輸出: 4 - 20 mA 0 - 10 V	測壓力和拉力  力度: 0.02 - 50 kN 材質: 鋁, 不銹鋼 輸出: 2 mV/V 0 (4) - 20 mA / 0 - 10 VDC
--	---	--	--	---	--

電氣式測力傳感器系列